# Table of Contents

**JQueryRating** ..... **1**
Usage ..... 1
Formfield rating ..... 1
Examples ..... 1

# JQueryRating

Homepage: http://www.fyneworks.com/jquery/star-rating/
Author(s): Diego A. (Fyneworks.com)
Version: 3.12

The Star Rating Plugin is a plugin for the jQuery Javascript library that creates a non-obstrusive star rating control based on a set of radio input boxes.

It turns a collection of radio boxes into a neat star-rating control. It creates the interface based on standard form elements, which means the basic functionality will still be available even if Javascript is disabled.

## Usage

Create a set of radio buttons and surround them with a div of class **`jqRating`**. When you hover over the stars, a tooltip at the right side will display the value of the radio box, or the title if present.

## Formfield `rating`

The jquery rating plugin is used to implement a **`rating`** formfield. Here are some examples:

| Name | Type | Size | Values | Tooltip message | Attributes |
|---|---|---|---|---|---|
| Rating1 | rating | 10 | very low, low, substandard, standard, superior, I like it, quite good, good, very good, excellent | | |
| Rating2 | rating | 20 | 0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 9.5, 10 | | split:2 |
| Rating3 | rating+values | 10 | very low=1, low=2, substandard=3, standard=4, superior=5, I like it=6, quite good=7, good=8, very good=9, excellent=10 | | |

- Rating1 defines a simple scheme using named categories.
- Rating2 defines a selection between 0-10 using 0.5 steps
- Rating3 defines a numeric rating where each value is mapped to a named category

Note, that the Attributes column of a rating field will be used to parametrize the jquery rating plugin.

## Examples

```
%STARTSECTION{"markup"}%
<div class="jqRating">
<input type="radio" name="test" value="1" class="rating" title="very low"/>
<input type="radio" name="test" value="2" class="rating" title="low" />
<input type="radio" name="test" value="3" class="rating" title="substandard" />
```

```
<input type="radio" name="test" value="4" class="rating" title="standard" />
<input type="radio" name="test" value="5" class="rating" title="superior" checked="checked
<input type="radio" name="test" value="6" class="rating" title="I like it" />
<input type="radio" name="test" value="7" class="rating" title="quite good" />
<input type="radio" name="test" value="8" class="rating" title="good" />
<input type="radio" name="test" value="9" class="rating" title="very good" />
<input type="radio" name="test" value="10" class="rating" title="excelent" />
</div>
%ENDSECTION{"markup"}%
```

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r4 - 08 Feb 2010 - 22:36:29 - ProjectContributor

- . System
- Log In

- **Toolbox**
- Users
- Groups
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences

- **User Reference**
- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**
- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**
- Public
- System

Copyright © by the contributing authors. All material on this site is the property of the contributing authors.
Ideas, requests, problems regarding Wiki? Send feedback